



## PRESS RELEASE

For Immediate Release

November 28, 2011

[www.noburn.com](http://www.noburn.com)

Contact: Lindsay Lenze

### No-Burn® Plus XD Approved at Lowest Wet Mil Thickness Over Sealection® 500

PLUS XD COATING OVER FOAM PLASTIC INSULATION SYSTEM MEETS AC 377 APPENDIX X REQUIREMENTS AT LOWEST WET MIL THICKNESS

No-Burn® Plus XD is now approved over Demilec's Sealection® 500 at the lowest tested wet mil thickness, surpassing previous results. The test was performed in accordance with AC 377 Appendix X. Plus XD, used in lieu of a prescribed ignition barrier, applied at a thickness of 6 mils wet (4 mils dry). At this thickness, No-Burn Plus XD will cover approximately 267 sq. ft. per gallon.

"Offering our intumescent coating to Demilec installers at this thickness in the short-term means competitive bids and more awards" said Bill Kish, CEO of No-Burn, Inc. "Long-term, No-Burn, Inc. and Demilec continue to thrive as both the coatings and spray polyurethane foam markets experience continued growth. Our partnership brings building owners, suppliers and contractors domestically manufactured products at valued rates."



No-Burn® Plus XD is a low VOC intumescent coating manufactured in the USA; meeting both International Building Code (IBC) and International Residential Code (IRC) specific requirements for spray applied foam plastic insulation systems, while contributing to LEED regional material points and complying with the ARRA Buy American provision, Plus XD is available directly through Demilec USA and Service Partners nationwide. Technical questions about Plus XD should be directed to the manufacturer, No-Burn, Inc. Estimating and technical support are provided by No-Burn, Inc. No-Burn® applicators are invited to take the comprehensive online training. Email [info@noburn.com](mailto:info@noburn.com) for direct customer support and training access. Refer to the manufacturer's Technical Data Sheet for PPE, spray rig recommendations and application preparation.

#### **About No-Burn, Inc.**

No-Burn, Inc. has been leading the way in fire resistant technology since 1998. All No-Burn® products are evaluated by independent third party laboratories for compliance with International Codes. No-Burn's products are low VOC, non-toxic and non-carcinogenic and contribute to the enhancement of the built environment. Several No-Burn® products also offer a dual level of protection, reducing the risk of fire and resisting the growth of toxic-black mold. To learn more, please visit our website: [www.noburn.com](http://www.noburn.com). Contact No-Burn, Inc.'s sales and technical support at, [info@noburn.com](mailto:info@noburn.com) or call 800-989-8577.

#### **About DEMILEC (USA) LLC®**

DEMILEC (USA) LLC.® is a manufacturer of a line of high quality spray foam insulation products that include products and brands such as SEALECTION® 500, SEALECTION Agribalance® and HEATLOK SOY® 200. Anyone seeking more information about DEMILEC (USA) LLC.® or its products can visit [www.DemilecUSA.com](http://www.DemilecUSA.com) or call 1-877-DEMILEC (336-4532).

###